



DESCRIPTION

The BAT46W is available in SOD-123FL Package

ORDERING INFORMATION

Package Type	Part Number
SOD-123FL	BAT46W
Note	SPQ:3,000pcs/Reel
AiT provides all RoHS Compliant Products	

PIN DESCRIPTION



FEATURES

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- Available in SOD-123FL Package

MECHANICAL DATA

Case: SOD-123FL

Terminals: Solderable per MIL-STD-750,
Method 2026

Approx. Weight: 15mg, 0.00048oz



ABSOLUTE MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%

Parameter	Symbol	BAT46W	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	100	V
Maximum RMS Voltage	V_{RMS}	70	V
Maximum DC Blocking Voltage	V_{DC}	100	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	0.5	A
Peak Forward Surge Current 8.3ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	30	A
Max Instantaneous Forward Voltage at 1A	V_F	0.85	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	0.2 5	mA
Typical Junction Capacitance ^{NOTE1}	C_J	80	pF
Typical Thermal Resistance ^{NOTE2}	$R_{\theta JA}$	115	°C/W
Operating Junction Temperature Range	T_J	-55 ~ 125	°C
Storage Temperature Range	T_{STG}	-55 ~ 150	°C

NOTE1: Measured at 1MHz and applied reverse voltage of 4V D.C

NOTE2:P.C.B. mounted with 0.2 X 0.2" (5 X 5 cm) copper pad areas.



TYPICAL CHARACTERISTICS

Figure 1. Forward Current Deration Curve




Figure 2. Typical Reverse Characteristics




Figure 3. Typical Forward Characteristic




Figure 4. Typical Junction Capacitance




Figure 5. Maximum Non-Repetitive Peak Forward Surge Current





Figure 6. Typical Transient Thermal Impedance







PACKAGE INFORMATION

Dimension in SOD-123FL Package (Unit: mm)

Plastic surface mounted package; 2 leads



The recommended mounting pad size



Unit: $\frac{\text{mm}}{\text{(mil)}}$

UNIT		A	C	D	E	e	g	H _E	\angle
mm	Max	1.1	0.20	2.9	1.9	1.1	0.9	3.8	7°
	Min	0.9	0.12	2.6	1.7	0.8	0.7	3.5	
mil	Max	43	7.9	114	75	43	35	150	
	Min	35	4.7	102	67	31	28	138	



IMPORTANT NOTICE

AiT Components (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Components' integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or server property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Components assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.